



BERTEC®
for flexible fixation

Water-based degreaser

General

Universal cleaning agent/degreaser for the pretreatment and maintenance of all soiled surfaces. Also suitable for preparing surfaces before painting to improve adhesion. Suitable for use with water-based and technical paints.

Applications

Suitable for porous and non-porous surfaces. Removes soot, nicotine, grease and deposits...
Suitable for indoor and outdoor use.

Properties

Flash point	➤ 100°C
shine	N/A
Drying time	N/A
Specific gravity	Ca. 1,00g/cm ³
Return	N/A
Solvent	water

Instructions for use

Apply to a soiled but dry surface.
Leave to act for 10 to 20 minutes.
Can also be used as a cleaning solution with a pressure washer.
Do not use below 5°C.

Packaging and colours

Colour	Article number	EAN Code	Packaging	Volume
Transparant	WBD05		Bidon	5 L

TECHNISCHE FICHE



BERTEC®
for flexible fixation

Shelf life

Shelf life	2 years
Storage	Keep away from direct sunlight; do not freeze

Safety instructions

Avoid prolonged skin contact. Always wash hands thoroughly. In case of eye contact, rinse thoroughly with water for an extended period. Consult the safety data sheet for detailed information.

The information in this technical data sheet is based on our knowledge and experience and is of a general nature. This information is indicative and does not constitute a guarantee. It is the user's responsibility to ensure that the product is suitable for the intended application. Liability shall never exceed the limits specified in our terms and conditions of sale. Under no circumstances shall Bertec BV be liable for any consequential damage.